i-H SERIES

2D CNC Wire Bender





ipautomationinc.com Phone: (630)656-1215 Email: sales@ipautomationinc.com 400 E Fullerton Avenue, Carol Stream, IL, 60188 The i-H series 2D bender features robust all-electric design and easy to use Intellibend software for exceptional performance and reliability.



Intellibend Software Features

- Length-Rotation-Angle program format
- Streamlined dashboard with live production metrics
- 18.5" (47cm) Multi-touch screen
- Remote connectivity through secure VPN tunnel
- Seamless robotic integration to bender
- User access levels
- Intelligent maintenance driven by real-time usage
- OPC-UA protocol for industry 4.0 and IIOT



Accessories



kVA Butt Welder



Intellibend Robot

Technical Data

Model	Wire Diameter (Tensile)	Bend Radii	Bend Back Clearance
i6-H	2-6mm (620N/mm²)	2-8	36" (.9m) std. up to 83" (2.1m) available
i8-H	2.5-8mm (620N/mm²)	8-16	36" (.9m) std. up to 83" (2.1m) available
i10-H	3-10mm (620N/mm²)	8-16	48" (1.2m) std. up to 83" (2.1m) available
i13-H	4-13mm (620N/mm²)	8-16	48" (1.2m) std. up to 83" (2.1m) available

Phone: (630)656-1215
Email: sales@ipautomationinc.com
Website: ipautomationinc.com

Headquarters
400 E Fullerton Avenue,
Carol Stream, IL 60188, USA

Global Locations

- Querétaro, Mexico
- Czechia